

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~striketrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1, 10, 20 and 21 in accordance with the following:

1. (Currently Amended) A bread maker including a heating system and a kneading system, comprising:
 - a main body having an oven compartment;
 - an oven including a rear part and a side part accommodated in the oven compartment of the main body;
 - a spacing part provided between the main body and the oven to form a space between the main body and the oven and used to combine the main body and the oven, the spacing part protruding toward the rear part of the oven to form ~~the a space in which the insulation member is interposed~~; and
 - an insulation member interposed in the space between the main body and the oven, wherein the kneading system kneads dough and the heating system generates heat in the oven to make bread from the dough.
2. (Previously Presented) The bread maker according to claim 1, wherein
 - at least one first protruding part formed with a first screw hole; and
 - at least one first screw passing through the main body and inserted into the first screw hole of the respective first protruding part.
3. (Original) The bread maker according to claim 1, wherein
 - the spacing part protrudes towards the side part of the oven to form the space in which the insulation member is interposed,
 - at least one second protruding part formed with a second screw hole; and
 - at least one second screw passing through the main body and inserted into the second screw hole of the respective second protruding part.
4. (Original) The bread maker according to claim 2, wherein

the spacing part protrudes towards the side part of the oven to form the space in which the insulation member is interposed;

at least one second protruding part formed with a second screw hole; and

at least one second screw passing through the main body and inserted into the second screw hole of the respective second protruding part.

5. (Previously Presented) The bread maker according to claim 1, wherein

at least one first bracket formed with a first screw hole; and

at least one first screw passing through the main body and inserted into the first screw hole of the respective first bracket.

6. (Previously Presented) The bread maker according to claim 1, wherein

the spacing part protrudes towards the side part of the oven to form the space in which the insulation member is interposed,

at least one bracket formed with a screw hole; and

at least one screw passing through the main body and inserted into the screw hole of the bracket.

7. (Original) The bread maker according to claim 5, wherein

the spacing part protrudes towards the side part of the oven to form the space in which the insulation member is interposed;

at least one second bracket formed with a second screw hole; and

at least one second screw passing through the main body and inserted into the second screw hole of the respective second bracket.

8. (Original) The bread maker according to claim 1, further comprising:

a frame forming an oven compartment of the main body;

a frame cover to cover the outside of the frame; and

a control panel to allow a user to control the bread maker and to view an operating state of the bread maker.

9. (Original) The bread maker according to claim 8, wherein a side of the spacing part is adjacent to the frame of the oven to form the space in which the insulation member is interposed.

10. (Currently Amended) The bread maker including a heating system and a kneading system, comprising:

an oven including a rear part and a side part;

an oven compartment;

a frame forming the oven compartment; and

a spacing part provided between the frame and the oven to combine the frame with the oven, and to form a predetermined space to interpose an insulation;

wherein the spacing part protrudes towards the frame to form a space in which the insulation member is placed,

wherein the kneading system kneads dough and the heating system generates heat in the oven to make bread from the dough.

11. (Cancelled)

12. (Previously Presented) The bread maker according to claim 10, the spacing part further comprising:

at least one first protruding part formed with a first screw hole; and

at least one first screw passing through the main body and inserted into the first screw hole of the respective first protruding part.

13. (Original) The bread maker according to claim 8, wherein on the side part of the oven, the spacing part protrudes towards the frame to form a space in which the insulation member is placed.

14. (Original) The bread maker according to claim 13, the spacing part further comprising:

at least one second protruding part formed with a second screw hole; and

at least one second screw passing through the main body and inserted into the second screw hole of the respective second protruding part.

15. (Original) A bread maker according to claim 1, wherein the spacing part includes at least one first bracket formed with a first screw hole.

16. (Original) The bread maker according to claim 10, wherein the spacing protrudes towards the rear part of the oven to form the space in which the insulation member is interposed;

at least one first bracket formed with a first screw hole; and

at least one first screw passing through the main body and inserted into the first screw hole of the respective first protruding part.

17. (Original) The bread maker according to claim 16, wherein the spacing protrudes towards the side part of the oven to form the space in which the insulation member is interposed,

at least one second bracket formed with a second screw hole; and

at least one second screw passing through the main body and inserted into the second screw hole of the respective second protruding part.

18. (Previously Presented) The bread maker according to claim 10, the spacing part further comprising:

at least one first bracket formed with a first screw hole; and

at least one first screw passing through the main body and inserted into the first screw hole of the respective second protruding part.

19. (Original) The bread maker according to claim 18, the spacing part further comprising:

at least one second bracket formed with a second screw hole; and

at least one second screw passing through the main body and inserted into the second screw hole of the respective second protruding part.

20. (Currently Amended) A bread maker including an oven compartment, a heating system and a kneading system, comprising:

a frame to form the oven compartment; and

an oven including a rear part and a side part accommodated in the oven compartment, and separated by a space from the frame, the space being formed by a spacing part protruding toward the frame; and

an insulation provided between the frame and the oven which combines the frame with the oven,

wherein the kneading system kneads dough and the heating system generates heat in the oven to make bread from the dough.

21. (Currently Amended) A bread maker including an oven compartment, a heating system, comprising:

a frame to form the oven compartment;

a kneading system including at least one kneading drum for kneading dough;

an oven including a rear part and a side part accommodated in the oven compartment, and separated by a space from the frame, the oven providing heat from the heating system to make bread from the dough; and

a spacing part provided between the frame and the oven to form a space between the frame and the oven; and

an insulation provided between the frame and the oven in the space between the frame and the oven, which combines the frame with the oven.